



MODEL NO.	SWITCH FUNCTION			TERMINAL QUANTITY	CONNECTED TERMINALS		
	POS.1	POS.1	POS.1		POS.1	POS.1	POS.1
712B	ON	NONE	ON	12P	1-2,4-5 7-8,10-11	—	2-3,5-6 8-9,11-12
712F	(ON)	NONE	ON	12P	1-2,4-5 7-8,10-11	—	2-3,5-6 8-9,11-12
712C	ON	OFF	ON	12P	1-2,4-5 7-8,10-11	—	2-3,5-6 8-9,11-12
712H	MOM	OFF	ON	12P	1-2,4-5 7-8,10-11	—	2-3,5-6 8-9,11-12
712G	MOM	OFF	MOM	12P	1-2,4-5 7-8,10-11	—	2-3,5-6 8-9,11-12

MOM=MOMENTARY

SPECIFICATION

- PATING:10A 250VAC,15A 125VAC
15A 250VAC,20A 125VAC
- INSULATION RESISTANCE:DC 500V 200M Ω OR MORE
- CONTACT RESISTANCE:DC 2-4V 1A 20M Ω OR LESS
- WITHSTAND VOLTAGE:AC 1500V OR MORE

端子種類 Termination Options

H	S	Q	T	P

產品
PRODUCT
比例
SCALE

POWER TOGGLE SWITCH

1 : 1 單位
UNIT

MM

公差
TOLERANCE

±0.3MM LING PAO ENTERPRISE CO.,LTD

專吉精密工業股份有限公司
TRANKEY MICRO-TECH CORP